

## Specification

	<b>1GM10</b>	<b>2YM15</b>	<b>3YM20</b>	<b>3YM30</b>
<b>Cylinders</b>	1	2	3	3
<b>Maximum Output</b>	<b>9.0mhp</b> @ 3600rpm	<b>14mhp</b> @ 3600rpm	<b>21mhp</b> @ 3600rpm	<b>29mhp</b> @ 3600rpm
<b>Cooling System</b>	Direct sea water cooling	Freshwater H/E	Freshwater H/E	Freshwater H/E
<b>Bore x Stroke</b>	75 x 72 mm	70 x 74 mm	70 x 74 mm	76 x 82 mm
<b>Displacement</b>	0.318 litres	0.570 litres	0.854 litres	1.115 litres
<b>Reduction (Fwd) &amp; ModelGear</b>	2.21/2.62/3.22:1	2.21/2.62/3.22:1	2.21/2.62/3.22:1	2.21/2.62/3.22:1
	KM2P-1	KM2P-1	KM2P-1	KM2P-1
<b>Dry Weight (Engine &amp; transmission)</b>	81 kg	113 kg	130 kg	133 kg
<b>Direction of rotation</b>	<b>Crankshaft</b>	Counter-clockwise viewed from stern		
	<b>Propeller shaft</b>	Clockwise viewed from stern		
*Note optional vee drive 15 ° down angle transmissions available for YM series Optional 8 ° down angle transmission available for GM & YM series.				