

Specification

		4JH4TE			4JH4-HTE			4JH3-DTE	
Class		4JH4-TFE	4JH4-TBE	4JH4-TIE	4JH4-HTFE	4JH4-HTBE	4JH4-HTIE	4JH3-DTHE	4JH3-DTHE1
Configuration		4-stroke, vertical , water cooled - direct injection							
Cylinders		4 in-line			4 in-line			4 in-line	
Maximum Output		75mhp @ 3200rpm			110mhp @ 3200rpm			125mhp @ 3800rpm	
Cooling System		Freshwater cooling by centrifugal freshwater pump and rubber impeller sea water pump							
Bore x Stroke		84 x 90 mm			84 x 90 mm			84 x 90 mm	
Displacement		1.995 litres			1.995 litres			1.995 litres	
Aspiration		Turbocharged			Turbocharged with intercooler				
Dry Weight		235 kg	237 kg	237 kg	245 kg	247 kg	248 kg	260 kg	259 kg
Reduction (FWD) & Model of Gear		ZF30M	KM4A2	ZF25A	ZF30M	KM4A2	ZF25A	KMH4A	ZF25A
		2.15 / 2.70	1.47 / 2.14 / 2.63	2.00 / 2.48	2.15 / 2.70	1.47 / 2.14 / 2.63	2.00 / 2.48	2.04/2.45	2.00 / 2.48
Direction of Rotation	C/S	CCW viewed from stern							
	P/S	CW	Bi Rotation	Bi Rotation	CW	Bi Rotation	Bi Rotation		Bi Rotation