

## Specifications for KMG65E

		KMG65E-S3, S6	KMG65E-K3, K6		
<b>Voltage</b>		230Vac			
<b>System Output</b>		50Hz			
<b>Mass of Main Parts</b>	<b>Generator</b>	21 kg (46.3lb)	20.5 kg (45.2lb)		
	<b>Power box</b>	13kg (28.7lb)			
<b>Dimensions</b>		320 x 360 x 145 mm			
<b>Power Consumption of the Power Box</b>		<3A (12Vdc)			
<b>Applied Sail Drive or Marine Gear</b>		SD 50	KM35P, A (2)		
<b>Applied Engine Model</b>		3JH4E, 4JH4AE			
<b>Permissible Input Speed</b>		3500min-1			
		<b>KMG65E-S3</b>	<b>KMG65E-K3</b>	<b>KMG65E-S6</b>	<b>KMG65E-K6</b>
<b>QTY of Connected Power Box</b>		1		2	
<b>Continuous Output</b>		3.0kVA (3.0kW)		6.0 (3.0 and 3.0)kVA (6.0 (3.0 and 3.0)kW)	
<b>Power Factor</b>		1			
<b>Maximun Output</b>		3.2kVA (3.2kW)		6.4 (3.2 and 3.2)kVA (6.4 (3.2 and 3.2)kW)	
<b>Start/Stop</b>		Manual switch at panel			
<b>Warning Signal (LED)</b>		Generator Temperature, Power Box Temperature, Overload, Insufficient Speed			
<b>Self Protection Function</b>		Auto stop for overheat and overload			